


SMA Plug to SMA Plug, KF240 Microwave Cable, 600mm

240X-SMMSMM-600

FEATURES

- Suitable up to 18GHz
- Excellent Return Loss & Insertion Loss
- Ultra Low Loss, Phase Stable & Amplitude Stable
- 100% VNA Tested; supplied with serialised performance plots
- Heavy Duty Sleeving for Reliability and Robustness



MATERIAL SPECIFICATION

Cable Series	GTx KF240, Microwave Coaxial Cable
Connector 1	SMA Straight Plug, Stainless Steel
Connector 2	SMA Straight Plug, Stainless Steel
Length	600mm (Tip to Tip)
Cable Overall Diameter	6.50mm
Armour	None

ELECTRICAL SPECIFICATION

Impedance	50 Ohms
Max. Frequency	18 GHz
VSWR	1.35 @18 GHz
Insertion Loss	1.55dB @18 GHz
Velocity of Propagation	70%
Voltage Withstanding	2500V RMS Maximum
Shielding Effectiveness	> 90dB

MECHANICAL & ENVIRONMENTAL SPECIFICATION

Bending Radius (static)	33mm
Bending Radius (flexing)	65mm
Cable Weight	142 gms/m
RoHS Compliant	Yes
Temperature Range	-55 to +125 degrees C